

WHAT IS CLAIMED IS:

1. A radio communication system comprising:

(a) at least one mobile station;

(b) a plurality of base stations configured to generate a  
5 plurality of beam patterns; and

(c) a base station controller which is connected to the  
plurality of base stations, and then assigns a fixed channel to each mobile  
station, controls the beam patterns of the base stations and accordingly  
carries out a radio communication with the mobile station, the base  
10 station controller having a device which when carrying out a  
transmission and a reception to and from a different mobile station to  
which the same channel is assigned, controls the beam patterns so that  
the channels do not interfere with each other.

15 2. A radio communication system of claim 1,

wherein the mobile station is a mobile station running on a road,  
and at least a part of the plurality of base stations are arranged along the  
road.

20 3. A radio base station controller which is connected to a  
plurality of base stations configured to generate a plurality of beam  
patterns, and then controls an antenna that is installed in each of the  
base stations and composed of a plurality of antenna devices, and  
accordingly carries out a radio communication with a mobile station, the  
25 radio base station controller comprising:

(a) an antenna controller configured to control the antenna in  
each of the base stations; and

(b) at least one modulating/demodulating device configured  
to modulate and demodulate a signal which is transmitted to and  
30 received from the mobile station.

4. A radio base station controller of claim 3, wherein the  
antenna controller comprises:

a selector configured to select at least one antenna device from  
35 the plurality of base stations; and

a setter configured to set a weight of the selected antenna device.

5. A radio base station controller of claim 4, wherein the setter has a device configured to determine the weight of the antenna device so that when a transmission or a reception is carried out to or from a different mobile station to which the same channel is assigned.

6. A radio base station controller of claim 4, wherein the antenna controller further has a measuring device configured to measure respective reception strengths of the respective antenna devices in the plurality of base stations.

7. A radio base station controller of claim 3, wherein the mobile station is a mobile station running on a road, and at least a part of the plurality of base stations are arranged along the road.

8. A radio base station controller which is connected to a plurality of base stations arranged along a road, and then controls the plurality of base stations, and accordingly carries out a radio communication with at least one mobile station running on the road, the radio station controller comprising:

(a) a device configured to assign the same channel to each mobile station of the same speed or the same lane;

(b) a device configured to detect at least one of the speed and the lane of the mobile station; and

(c) a device which when the speed or the lane of the mobile station is changed, changes an assignment channel, in accordance with a speed or a lane after the change.

9. A radio base station controller of claim 8, wherein a communication interval is changed depending on the change of the speed of the mobile station.

10. A radio mobile station which is connected to a plurality of

base stations configured to generate a plurality of beam patterns, and then carries out a radio communication with a base station controller that can control an antenna installed in each of the base stations and composed of a plurality of antenna devices,

5            wherein the radio mobile station transmits a signal including at least information to identify the radio mobile station, even if there is not a signal to be transmitted to the base station controller.

11.        A radio base station controller which is connected to a  
10   plurality of base stations arranged along a road, and then controls the plurality of base stations and accordingly carries out a radio communication with at least one mobile station running on the road,

          wherein a boundary between radio base station controllers adjacent to each other is positioned in a portion in which a movement  
15   destination of the mobile station on the road can be pointed out.

12.        A radio communication system comprising:

(a)        at least one mobile station having a device configured to select, from a plurality of same reception signals, a reception signal in  
20   which a reception state is better;

(b)        a first base station controller having a device configured to detect a start of a communication between a predetermined first base station and a mobile station, a device configured to request a hand-over process to the mobile station, and a device configured to transfer a  
25   transmission signal to the mobile station to a base station controller of a hand-over destination of the mobile station, the first base station controller connected to a first base station group including the predetermined first base station; and

(c)        a second base station controller having a device  
30   configured to transmit the transmission signal transferred from the first base station controller, through a predetermined second base station to the mobile station, the second base station controller connected to a second base station group including the predetermined second base station.

35

13. A radio communication system of claim 12, wherein the predetermined first and second base stations are arranged close to a boundary between the first and second base station controllers.

5 14. A radio communication system of claim 12, wherein the mobile station is a mobile station running on a road, and

at least a part of the first and second base station groups including the predetermined first and second base stations is positioned in a portion in which a movement destination of the mobile station on the  
10 road can be pointed out.

15 15. A radio communication system of claim 14, wherein the first base station controller further comprises:

a device configured to detect a speed of the mobile station; and

15 a device configured to change the predetermined first base station, in accordance with the detected speed.

20 16. A radio communication system of claim 14, wherein the first and second base station groups arranged along the road are arranged in a predetermined interval, and an interval between a first base station and a second base station which are the closest to each other is shorter than the predetermined interval.

25 17. A radio communication system of claim 14, wherein the first and second base station controllers select an optimal transmission rate and error correction code in accordance with a speed of the mobile station when performing a hand-over process on the mobile station, and then carry out a transmission and a reception to and from the mobile station.

30 18. A radio communication method comprising the steps of:

(a) detecting a start of a communication between a predetermined first base station connected to a first base station controller and a mobile station running on a road;

35 (b) requesting a hand-over process to the mobile station;

(c) transferring to a second base station controller, a signal to be transferred through the predetermined first base station to the mobile station;

(d) transmitting the signal to the mobile station through a  
5 predetermined second base station connected to the second base station  
controller; and

(e) selecting a signal in which a reception state is better, from two signals received by the mobile station.

10                    19.    A radio communication method of claim 18, wherein the  
predetermined first and second base stations are arranged close to a  
boundary between the first and second base station controllers.

20. A radio communication method of claim 19,  
15 wherein the first base station controller is connected to a first  
base station group including the predetermined first base station,  
the second base station controller is connected to a second base  
station group including the predetermined second base station, and  
at least a part of the first and second base station groups  
20 including the predetermined first and second base stations is arranged  
along a portion in which a movement destination of the mobile station on  
the road can be pointed out.